












International Power Cord Reels

Plug Photo	Retracting Cable and Plug	Fixed End Cable and Plug	Countries*	Part Number Spec Number
	10ft [3m], Gray, H05VV-F 3G 1.5mm ² , with molded 90° European CEE 7/7 (Type E/F) male plug	Gray, H05VV-F 3G 1.5mm ² , 30" [.75m], with stripped wire ends	Continental Europe (Germany, Spain, France, Belgium, Czech Rep., Finland, Norway, Sweden, Portugal, Greece)	300684-1 198755
	10ft [3m], Gray, H05VV-F 3G 1.5mm ² , with molded 90° British BS-1363A (Type G) male plug	Gray, H05VV-F 3G 1.5mm ² , 30" [.75m], with stripped wire ends	United Kingdom, UAE	300685-1 198756
	10ft [3m], Gray, H05VV-F 3G 1.5mm ² , with straight molded Danish Hospital Grade DK-2-8A male plug	Gray, H05VV-F 3G 1.5mm ² , 30" [.75m], with stripped wire ends	Denmark (Hospital Grade)	300686-1 198757
	10ft [3m], Gray, H05VV-F 3G 1.5mm ² , with straight molded Danish AFSNIT 107-2-D1 (Type K) male plug	Gray, H05VV-F 3G 1.5mm ² , 30" [.75m], with stripped wire ends	Denmark (Industrial Grade)	300687-1 198758
	10ft [3m], Gray, H05VV-F 3G 1.5mm ² , with straight molded Brazilian NBR 14136 male plug	Gray, H05VV-F 3G 1.5mm ² , 30" [.75m], with stripped wire ends	Brazil	300688-1 198759
	15ft [4.5m], Gray, RVV 0.75mm ² , with straight molded Chinese CCC GB2099 male plug	Gray, H05VV-F 3G 0.75mm ² , 30" [.75m], with stripped wire ends	China	300689-1 198760
	15ft [4.5m], Orange, H05VV-F 3G 1.00mm ² , with clear straight molded Australian Hospital Grade AS/NZS 3112 (Type I) male plug	Orange, H05VV-F 3G 1.00mm ² , 12" [.30m], with spade terminals & ground ring	Australia	300690-1 198761
	15ft [4.5m], Gray, H05VV-F 3G 0.75mm ² , with straight molded Swiss SEV 1011 (Type J) male plug	Gray, H05VV-F 3G 0.75mm ² , 30" [.75m], with stripped wire ends	Switzerland	300691-1 198762
	15ft [4.5m], Gray, H05VV-F 3G 0.75mm ² , with 90° molded Indian IA6A3 (BS 546 6A Type D) male plug, complies with IS 1293:2005	Gray, H05VV-F 3G 0.75mm ² , 30" [.75m], with stripped wire ends	India	300692-1 198763
	15ft [4.5m], Gray, H05VV-F 3G 0.75mm ² , with 90° molded South African SANS 164-1 (16A BS 546 Type M, SABS approved) male plug	Gray, H05VV-F 3G 0.75mm ² , 30" [.75m], with stripped wire ends	South Africa	300693-1 198764
	15ft [4.5m], Gray, H05VV-F 3G 0.75mm ² , with molded 90° British BS-1363A (Type G) male plug	Gray, H05VV-F 3G 1.5mm ² , 36" [.9m], with stripped wire ends	United Kingdom, UAE	300736-1 198796